



Wall mounted unit

FTXA-BT + RXA-A / RXA-B

stylish



Coanda effect - cooling



Coanda effect - heating



Intelligent thermal sensor



Online controller



Multi model application

Where innovation meets creativity

- › Compact design in blackwood
- › Perfect temperature distribution thanks to Coanda effect
- › Intelligent thermal sensor: air flow is adjusted when detecting temperature differences
- › Online controller via app
- › Daikin Flash Streamer technology: powerful air purification
- › Practically inaudible
- › Bluevolution range: lower environmental impact
- › Seasonal efficiency values up to A+++ in cooling and heating

FTXA-BT + RXA-A / RXA-B



RXA-B

FTXA-BT

Efficiency data		FTXA + RXA	20BT + 20A	25BT + 25A	35BT + 35A	42BT + 42B	50BT + 50B
Cooling capacity	Min./Nom./Max.	kW	1.3 /2.0 /2.6	1.3 /2.5 /3.2	1.4 /3.4 /4.0	1.70 /4.20 /5.00	1.70 /5.00 /5.30
Heating capacity	Min./Nom./Max.	kW	1.30 /2.50 /3.50	1.30 /2.80 /4.70	1.40 /4.00 /5.20	1.70 /5.40 /6.00	1.70 /5.80 /6.50
Power input	Cooling	Min./Nom./Max.	kW	0.27 /0.43 /0.63	0.27 /0.56 /0.78	0.31 /0.78 /1.04	-/1.05 /-
	Heating	Min./Nom./Max.	kW	0.25 /0.50 /0.91	0.25 /0.56 /1.22	0.26 /0.99 /1.67	-/1.31 /-
Space cooling	Energy efficiency class			A+++			A++
	Capacity	Pdesign	kW	2.00	2.50	3.40	4.20
	SEER			8.75	8.74	8.73	7.50
	Annual energy consumption		kWh/a	80	101	137	196
Space heating (Average climate)	Energy efficiency class			A+++			A++
	Capacity	Pdesign	kW	2.40	2.45	2.50	3.80
	SCOP/A				5.15		4.60
	Annual energy consumption		kWh/a	653	666	680	1,150
Nominal efficiency	EER			4.70	4.46	4.37	3.99
	COP			5.00		4.04	4.12
	Annual energy consumption		kWh		-		526
	Energy labeling Directive	Cooling/Heating				A/A	

Nominal cooling capacities are based on: indoor temperature: 27°CDB, 19°CWB, outdoor temperature: 35°CDB, equivalent refrigerant piping: 5m, level difference: 0m. | Nominal heating capacities are based on: indoor temperature: 20°CDB, outdoor temperature: 7°CDB, 6°CWB, equivalent refrigerant piping: 5m, level difference: 0m. | See separate drawing for operation range | See separate drawing for electrical data

Indoor unit		FTXA	20BT	25BT	35BT	42BT	50BT		
Dimensions	Unit	HeightxWidthxDepth	mm						
			295 x798 x189						
Weight	Unit		kg						
			11.5						
Air filter	Type		Removable / washable						
Fan	Air flow rate	Cooling	Silent operation/Low/Medium/High	m³/min	4.6 /6.1 /8.2 /11.0	4.6 /6.1 /8.6 /11.5	4.6 /6.1 /8.6 /11.9	4.6 /7.2 /9.8 /13.1	5.2 /7.6 /10.4 /13.5
		Heating	Silent operation/Low/Medium/High	m³/min	4.5 /6.4 /8.7 /10.9	4.5 /6.4 /9.0 /11.1	4.5 /6.4 /9.0 /11.5	5.2 /7.7 /10.5 /14.6	5.7 /8.2 /11.1 /15.1
Sound power level	Cooling			57		60			
Sound pressure level	Cooling	Silent operation/Low/High	dBA	19 /25 /39	19 /25 /40	19 /25 /41	21 /29 /45	24 /31 /46	
	Heating	Silent operation/Low/High	dBA	19 /25 /39	19 /25 /40	19 /25 /41	21 /29 /45	24 /33 /46	
Control systems	Infrared remote control			ARC466A58					
	Wired remote control			BRC073					

Outdoor unit		RXA/RXA	20A	25A	35A	42B	50B
Dimensions	Unit	HeightxWidthxDepth	mm				
			550 x765 x285				
Weight	Unit		kg				
			32				
Sound power level	Cooling		59		61	62.0	
	Heating		59		61	62.0	
Sound pressure level	Cooling	Nom.	46		49	48.0	
	Heating	Nom.	47		49	48.0	
Operation range	Cooling	Ambient	Min.~Max.	°CDB			
	Heating	Ambient	Min.~Max.	°CWB			
Refrigerant	Type		R-32				
	GWP		675.0				
	Charge	kg/TCO2Eq	0.76 /0.52				1.10 /0.75
Piping connections	Liquid	OD	mm				
			635				
	Gas	OD	mm				
			9.50				
	Piping length	OU - IU Max.	m				
		20					
	Additional refrigerant charge	kg/m	0.02 (for piping length exceeding 10m)				
	Level difference	IU - OU Max.	m				
			15.0				
Power supply	Phase/Frequency/Voltage	Hz/V	1~/50 /220-240				
Current - 50Hz	Maximum fuse amps (MFA)	A	-				

Contains fluorinated greenhouse gases | See separate drawing for operation range | See separate drawing for electrical data

Daikin Europe N.V. Naamloze Vennootschap · Zandvoordestraat 300 · 8400 Oostende · Belgium · www.daikin.eu · BE 0412 120 336 · RPR Oostende (Responsible Editor)



Daikin Europe N.V. participates in the Eurovent Certified Performance programme for Fan Coil Units and Variable Refrigerant Flow systems. Check ongoing validity of certificate: www.eurovent-certification.com

ECPEN20-052 02/2020



The present publication is drawn up by way of information only and does not constitute an offer binding upon Daikin Europe N.V. Daikin Europe N.V. has compiled the content of this publication to the best of its knowledge. No express or implied warranty is given for the completeness, accuracy, reliability or fitness for particular purpose of its content and the products and services presented therein. Specifications are subject to change without prior notice. Daikin Europe N.V. explicitly rejects any liability for any direct or indirect damage, in the broadest sense, arising from or related to the use and/or interpretation of this publication. All content is copyrighted by Daikin Europe N.V.