

Wall mounted unit

FTXP-M / FTXP-M9



comfora



Practically inaudible



Energy saving during standby mode



3-D air flow



Online controller via app



Multi model application

Discreet wall mounted unit providing high efficiency and comfort

- › Practically inaudible
- › Online controller (optional)
- › Silver allergen removal and air purifying filter
- › 3-D airflow: air is blown into all corners of a room
- › Ideal for above door installation

- › Bluevolution range: lower environmental impact
- › Seasonal efficiency values up to A++ in cooling and heating
- › Space saving contemporary wall mounted design

FTXP-M9 / FTXP-M + RXP-M



FTXP20-71M9



RXP-M



ARC480A11

Indoor unit		FTXP/FTXP		20M9	25M9	35M9	50M	60M	71M	
Dimensions	Unit	HeightxWidthxDepth		286 x770 x225			295 x990 x263			
Weight	Unit			8.50			9.00			
Air filter	Type			Removable / washable						
Fan	Air flow rate	Cooling	Silent operation/Low/Medium/High	m ³ /min	4.2 /5.6 /7.4 /9.5	4.2 /5.8 /7.7 /9.7	4.5 /6.3 /8.3 /11.5	8.3 /11.5 /14.0 /16.3	9.2 /11.8 /14.4 /16.8	10.1 /11.8 /14.4 /16.8
		Heating	Silent operation/Low/Medium/High	m ³ /min	5.2 /6.2 /8.1 /10.4	5.2 /6.4 /8.1 /10.4	5.3 /7.0 /9.0 /11.5	10.4 /11.8 /14.4 /17.3	11.0 /12.4 /15.3 /17.9	
Sound power level	Cooling			dBA	55			58		
	Heating			dBA	55			58		
Sound pressure level	Cooling	Silent operation/Low/High		dBA	19 /25 /39	19 /26 /40	20 /27 /43	27 /34 /43	30 /36 /45	32 /37 /46
	Heating	Silent operation/Low/High/Super high		dBA	21 /28 /39 /-	21 /28 /40 /-	21 /29 /40 /-	-30 /38 /42	-32 /40 /44	-33 /41 /45
Control systems	Infrared remote control		ARC480A53							
	Wired remote control		BRC944B2 / BRC073A1							

Outdoor unit		RXP		20M	25M	35M	50M	60M	71M			
Dimensions	Unit	HeightxWidthxDepth		550x658x275					734x870x373			
Weight	Unit			26			28					
Sound power level	Cooling			60					61			
	Heating			61					63			
Sound pressure level	Cooling	Nom./High		dBA					-46			
	Heating	Nom./High		dBA					-47			
Operation range	Cooling	Ambient	Min.-Max.	°CDB					-10~48			
	Heating	Ambient	Min.-Max.	°CWB					-15~24			
Refrigerant	Type	R-32										
	GWP	675.0										
	Charge	kg/TCO2Eq		0.55/0.37		0.70/0.48		0.90/0.61		1.15/0.78		
Piping connections	Liquid	OD	mm		6,35					6,4		
	Gas	OD	mm		9,5					12,7		
	Piping length	OU - IU	Max.		m					15		
	Additional refrigerant charge			kg/m							0.02 (for piping length exceeding 10m)	
	Level difference	IU - OU	Max.		m					12		
Power supply	Phase/Frequency/Voltage		Hz/V		1~/50/220-240							
Current - 50Hz	Maximum fuse amps (MFA)		A		-							

See separate drawing for operation range | See separate drawing for electrical data | Contains fluorinated greenhouse gases

Efficiency data		FTXP + RXP		20M9 + 20M	25M9 + 25M	35M9 + 35M	50M + 50M	60M + 60M	71M + 71M	
Cooling capacity	Min./Nom./Max.	kW		1.3/2.00/2.6	1.3/2.50/3.0	1.3/3.50/4.0	1.7/5.0/6.0	1.7/6.0/7.0	2.3/7.1/7.3	
Heating capacity	Min./Nom./Max.	kW		1.30/2.50/3.50	1.30/3.00/4.00	1.30/4.00/4.80	1.7/6.0/7.7	1.7/7.0/8.0	2.3/8.2/9.0	
Power input	Cooling	Min./Nom./Max.		kW	0.31/0.50/0.72	0.31/0.65/0.72	0.29/1.01/1.30	0.320/1.385/1.826	0.332/1.824/2.980	0.449/2.689/3.274
	Heating	Min./Nom./Max.		kW	0.25/0.52/0.95	0.25/0.69/0.95	0.29/1.00/1.29	0.440/1.579/2.356	0.456/1.928/2.787	0.617/2.571/3.306
Space cooling	Energy efficiency class		A++							
	Capacity	Pdesign	kW		2.00	2.50	3.50	5.0	6.0	7.1
	SEER			6.79		6.92		6.62		7.30
	Annual energy consumption	kWh/a		103		126		186		240
Space heating (Average climate)	Energy efficiency class		A++							
	Capacity	Pdesign	kW		2.20	2.40	2.80	4.60	4.80	6.20
	SCOP/A			4.65		4.61		4.64		4.40
	Annual energy consumption	kWh/a		662		728		845		1,463

Daikin Europe N.V. Naamloze Venootschap · Zandvoordestraat 300 · 8400 Oostende · Belgium · www.daikin.eu · BE 0412 120 336 · Oostende (Responsible Editor)



Daikin Europe N.V. participates in the Eurovent Certified Performance programme for Liquid Chilling Packages and Hydronic Heat Pumps, Fan Coil Units and Variable Refrigerant Flow systems. Check ongoing validity of certificate: www.eurovent-certification.com

ECPEN22-046

04/2022

The present leaflet is drawn up by way of information only and does not constitute an offer binding upon Daikin Europe N.V. Daikin Europe N.V. has compiled the content of this leaflet to the best of its knowledge. No express or implied warranty is given for the completeness, accuracy, reliability or fitness for particular purpose of its content and the products and services presented therein. Specifications are subject to change without prior notice. Daikin Europe N.V. explicitly rejects any liability for any direct or indirect damage, in the broadest sense, arising from or related to the use and/or interpretation of this leaflet. All content is copyrighted by Daikin Europe N.V.

