

# Wall mounted unit

FTXTP-K/RXTP-N



comfora



Guaranteed operation down to -25°C



Energy saving during standby mode



Online controller via app

## Wall mounted unit providing high efficiency and comfort

- › Guaranteed heating capacity at low ambient temperature, down to -25°C
- › Thanks to the unique free hanging coil of the outdoor unit, the defrost cycle is improved, resulting in lower running costs and no ice build-up
- › Developed for regions with severe winter conditions
- › The unit's compact dimensions makes it ideal for renovation projects, especially for above door installation

- › Seasonal efficiency values: full range A++ in cooling and heating
- › Online controller (optional): control your indoor from any location with an app, via your local network or internet and keep an overview on your energy consumption
- › Space saving contemporary wall mounted design

# FTXTP-K/RXTP-N + RXTP-N



Indoor unit		FTXTP	35K	25K
Casing	Colour		White	
Dimensions	Unit	HeightxWidthxDepth	mm	
			285x770x225	
Sound power level	Cooling		dBA	
	Heating		58	
Sound pressure level	Cooling	High/Medium/Low/Silent operation	dBA	
	Heating	High/Medium/Low/Silent operation	43/35 (1)/26/21	
Control systems	Infrared remote control		ARC480A11	
	Wired remote control		BRC944B2 / BRC073A1	

(1) Nominal heating capacities are based on: indoor temperature: 20°CDB, outdoor temperature: 7°CDB, 6°CWB, equivalent refrigerant piping: 5m, level difference: 0m. | See separate drawing for electrical data | Cooling: T2: indoor temp. 26,6°CDB, 19,4°CWB, outdoor temp. 48°CDB [Btu/hr/W]


Efficiency data		FTXTP + RXTP	35K + 35N	25K + 25N
Cooling capacity	Min./Nom./Max.	kW	0.70/3.50/4.40	0.70/2.50/4.00
Heating capacity	Min./Nom./Max.	kW	0.80/4.00/6.70	0.80/3.20/6.20
Power input	Cooling	Nom.	kW	0.91
	Heating	Nom.	kW	0.88
Space cooling	Capacity	Pdesign	kW	3.50
	Energy efficiency class			A++
	SEER		7.20	7.10
Space heating (Average climate)	Capacity	Pdesign	kW	3.00
	Energy efficiency class			A++
	SCOPnet/A		4.82	4.99
Nominal efficiency	Annual energy consumption	kWh/a	873	703
	EER		3.80	4.40
	COP		4.44	4.95

See separate drawing for electrical data | Cooling: T2: indoor temp. 26,6°CDB, 19,4°CWB, outdoor temp. 48°CDB [Btu/hr/W] | Nominal heating capacities are based on: indoor temperature: 20°CDB, outdoor temperature: 7°CDB, 6°CWB, equivalent refrigerant piping: 5m, level difference: 0m.

Outdoor unit		RXTP	35N	25N
Dimensions	Unit	HeightxWidthxDepth	mm	
			551x763x312	
Sound power level	Cooling		dBA	
	Heating		61	
Sound pressure level	Cooling	Nom.	dBA	
	Heating	Nom.	48	
Operation range	Cooling	Ambient	Min.-Max.	°CDB
	Heating	Ambient	Min.-Max.	-10~-46
Refrigerant	Type/Charge/GWP		kg/TCO <sub>2</sub> eq	
			R-32/1.1/-/675	
Power supply	Phase/Frequency/Voltage		Hz/V	
			1~/50/220-240	

Contains fluorinated greenhouse gases | See separate drawing for operation range | See separate drawing for electrical data

**Daikin Europe N.V.** Naamloze Vennootschap Zandvoordestraat 300 · 8400 Oostende · Belgium · www.daikin.eu · BE 0412 120 336 · RPR Oostende (Publisher)



CEPEN18-056 08/18



Daikin Europe N.V. participates in the Eurovent Certified Performance programme for Liquid Chilling Packages and Hydronic Heat Pumps, Fan Coil Units and Variable Refrigerant Flow systems. Check ongoing validity of certificate: www.eurovent-certification.com



The present publication is drawn up by way of information only and does not constitute an offer binding upon Daikin Europe N.V. Daikin Europe N.V. has compiled the content of this publication to the best of its knowledge. No express or implied warranty is given for the completeness, accuracy, reliability or fitness for particular purpose of its content and the products and services presented therein. Specifications are subject to change without prior notice. Daikin Europe N.V. explicitly rejects any liability for any direct or indirect damage, in the broadest sense, arising from or related to the use and/or interpretation of this publication. All content is copyrighted by Daikin Europe N.V.

Printed on non-chlorinated paper.